ΕN

PASSIONE BEAUTY S.P.A. REF 2014 - DL0172 NAIL PREP

Revision nr.2 Dated 20/09/2023 Printed on 20/09/2023 Page n. 1 / 12

Replaced revision:1 (Dated 18/09/2023)

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: REF 2014

Product name DL0172 NAIL PREP

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Nail prep

1.3. Details of the supplier of the safety data sheet

Name PASSIONE BEAUTY S.P.A.

Full address Viale Crispi 89-93

District and Country 36100 Vicenza (VI)

Italia

Tel. +39 0444-239569

e-mail address of the competent person

responsible for the Safety Data Sheet quality@pucosmetica.it

1.4. Emergency telephone number

For urgent inquiries refer to +39 0444-239569

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 2

Eye irritation, category 2

Highly flammable liquid and vapour.

Highly flammable liquid and vapour.

Causes serious eye irritation.

Causes skin irritation.

Specific target organ toxicity - single exposure, H336 May cause drowsiness or dizziness.

category 3

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:





Signal words: Danger

Hazard statements:

H225Highly flammable liquid and vapour.H319Causes serious eye irritation.H315Causes skin irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements:

Revision nr.2 Dated 20/09/2023 Printed on 20/09/2023 Page n. 2 / 12

Replaced revision:1 (Dated 18/09/2023)

SECTION 2. Hazards identification .../>>

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves/ protective clothing / eye protection / face protection.

P370+P378 In case of fire: use . . . to extinguish.

P261 Avoid breathing dust / fume / gas / mist / vapours / spray.

P233 Keep container tightly closed.

P312 Call a POISON CENTRE / doctor / . . . if you feel unwell.

Contains: PROPAN-2-OL

ETHYL ACETATE

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification x = Conc. % Classification (EC) 1272/2008 (CLP)

PROPAN-2-OL

INDEX 603-117-00-0 $24 \le x < 25,5$

EC 200-661-7 CAS 67-63-0

REACH Reg. 01-2119457558-25-xxxx

ETHYL ACETATE

INDEX 607-022-00-5 $21 \le x < 22.5$

EC 205-500-4 CAS 141-78-6

REACH Reg. 01-2119475103-46-00XX

ISOBUTYL ACETATE

INDEX 607-026-00-7 $21 \le x < 22.5$ Flam. Liq. 2 H225, EUH066, Classification note according to Annex VI to the

Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336

Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066

CLP Regulation: C

EC 203-745-1 CAS 110-19-0

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

Revision nr.2 Dated 20/09/2023 Printed on 20/09/2023 Page n. 3 / 12

Replaced revision:1 (Dated 18/09/2023)

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

Revision nr.2 Dated 20/09/2023 Printed on 20/09/2023 Page n. 4 / 12

Replaced revision:1 (Dated 18/09/2023)

SECTION 7. Handling and storage .../>>

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

Deutschland DEU Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und

Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung

gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56

ESP España Límites de exposición profesional para agentes químicos en España 2021

FRA France Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS

Decreto Legislativo 9 Aprile 2008, n.81 ITA Italia

GBR United Kingdom EH40/2005 Workplace exposure limits (Fourth Edition 2020) Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) OEL EU EU

2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive

2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive

91/322/EEC.

TLV-ACGIH ACGIH 2022

				B -0	2411221				
				PROI	PAN-2-OL				
hreshold Limit Valu									
Type C	Country	TWA/8h		STEL/15		Remarks / Ob	servations		
		mg/m3	ppm	mg/m3	ppm				
	DEU	500	200	1000	400				
	DEU	500	200	1000	400				
	SP	500	200	1000	400				
VLEP F	RA			980	400				
	SBR	999	400	1250	500				
TLV-ACGIH		492	200	983	400				
Predicted no-effect concentration - PNEC									
Normal value in fre						140,9	mg/l		
Normal value in ma	r					140,9	mg/l		
Normal value for fr	sediment					552	mg/kg/d		
Normal value for marine water sediment							552	mg/kg/d	
ealth - Derived no-	effect leve	I - DNEL /	DMEL						
	Effects on consumers					Effects on work	ers		
Route of exposure	Acute	e Acı	ıte	Chronic	Chronic	Acute local	Acute	Chronic	Chronic
	local	sys	temic	local	systemic		systemic	local	systemic
Oral					26				
					mg/kg bw/d				
Inhalation					89				500
					mg/m3				mg/m3
Skin					319				888
					mg/kg bw/d				mg/kg
					<u> </u>				bw/d

Revision nr.2 Dated 20/09/2023 Printed on 20/09/2023 Page n. 5 / 12 Replaced revision:1 (Dated 18/09/2023)

SECTION 8. Exposure controls/personal protection/>>

				ETHYL	ACETATE				
hreshold Limit	Value								
Type	Country	untry TWA/8h		STEL/15min		Remarks / Observations			
,,	,	mg/m	3 ppm	mg/m3	ppm				
AGW	DEU	730	200	1460	400				
MAK	DEU	750	200	1500	400				
VLA	ESP	734	200	1468	400				
VLEP	FRA	734	200	1468	400				
VLEP	ITA	734	200	1468	400				
WEL	GBR	734	200	1468	400				
OEL	EU	734	200	1468	400				
TLV-ACGIH		1441	400						
redicted no-effe	ect concentra	ation - P	NEC						
Normal value in fresh water							0,24	mg/l	
Normal value in marine water							0,024	mg/l	
Normal value for fresh water sediment						1,15	mg/kg/d		
Normal value for the terrestrial compartment							0,148	mg/kg/d	
lealth - Derived	no-effect lev	el - DNE	L / DMEL						
Effects on consumers					Effects on work	ers			
Route of expos			Acute	Chronic	Chronic	Acute local	Acute	Chronic	Chronic
	loca	ı	systemic	local	systemic		systemic	local	systemic
Oral					4,5 mg/kg bw/d				
Inhalation	734 mg/		734 mg/m3	367 mg/m3	367 mg/m3	1468 mg/m3	1468 mg/m3	734 mg/m3	734 mg/m3
Skin					37				63
					mg/kg bw/d				mg/kg

				ISOBUTY	L ACETATE			
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15r	nin	Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
AGW	DEU	300	62	600 (C)	124 (C)			
VLA	ESP	241	50	724	150			
VLEP	FRA	710	150	940	200			
VLEP	ITA	241	50	723	150			
WEL	GBR	724	150	903	187			
OEL	EU	241	50	723	150			
TLV-ACGIH			50		150			

lealth - Derived no-effe	ect level - Di	NEL / DMEL						
	Effects on	consumers			Effects on wor	kers		
Route of exposure	Acute	Acute	Chronic	Chronic	Acute local	Acute	Chronic	Chronic
	local	systemic	local	systemic		systemic	local	systemic
Oral		5		5				
		mg/kg bw/d		mg/kg bw/d				
Inhalation	300	300	35.7	35.7	600	600	300	300
	mg/m3	mg/m3	mg/m3	mg/m3	mg/m3	mg/m3	mg/m3	mg/m3
Skin		5		5		10		10
		mg/kg bw/d		mg/kg bw/d		mg/kg		mg/kg
						bw/d		bw/d

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on

Revision nr.2 Dated 20/09/2023 Printed on 20/09/2023 Page n. 6 / 12 Replaced revision:1 (Dated 18/09/2023)

SECTION 8. Exposure controls/personal protection/>>

the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required. Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value				
Appearance	liquid				
Colour	transparent				
Odour	pungent				
Melting point / freezing point	not available				
Initial boiling point	77 °C				
Flammability	not available				
Lower explosive limit	not available				
Upper explosive limit	not available				
Flash point	20 °C				
Auto-ignition temperature	not available				
Decomposition temperature	not available				
pH	not available				
Kinematic viscosity	not available				
Solubility	not available				
Partition coefficient: n-octanol/water	not available				
Vapour pressure	not available				
Density and/or relative density	not available				
Relative vapour density	not available				
Particle characteristics	not applicable				

Concentration: 2 %
Concentration: 11.4 %

Information

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

ETHYL ACETATE

Decomposes slowly into acetic acid and ethanol under the effect of light, air and water.

ISOBUTYL ACETATE

Decomposes under the effect of heat. Attacks various types of plastic materials.

Revision nr.2 Dated 20/09/2023 Printed on 20/09/2023 Page n. 7 / 12

Replaced revision:1 (Dated 18/09/2023)

SECTION 10. Stability and reactivity .../>>

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

ETHYL ACETATE

Risk of explosion on contact with: alkaline metals,hydrides,oleum.May react violently with: fluorine,strong oxidising agents,chlorosulphuric acid,potassium tert-butoxide.Forms explosive mixtures with: air.

ISOBUTYL ACETATE

Risk of explosion on contact with: strong oxidising agents. May react violently with: alkaline hydroxides, potassium tert-butoxide. Forms explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

ETHYL ACETATE

Avoid exposure to: light, sources of heat, naked flames.

ISOBUTYL ACETATE

Avoid exposure to: sources of heat,naked flames.

10.5. Incompatible materials

ETHYL ACETATE

Incompatible with: acids,bases,strong oxidants,chlorosulphuric acid.

ISOBUTYL ACETATE

Incompatible with: strong oxidants, nitrates, strong acids, strong bases.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:

ATE (Oral) of the mixture:

Not classified (no significant component)

Not classified (no significant component)

ATE (Dermal) of the mixture:

Not classified (no significant component)

PROPAN-2-OL

LD50 (Dermal): 12800 mg/kg Rat LD50 (Oral): 4710 mg/kg Rat

ETHYL ACETATE

LD50 (Oral): 5620 mg/kg ratt

ISOBUTYL ACETATE

LD50 (Dermal): > 17400 mg/kg rabbit LD50 (Oral): 13400 mg/kg rat

Revision nr.2 Dated 20/09/2023 Printed on 20/09/2023 Page n. 8 / 12

Replaced revision:1 (Dated 18/09/2023)

SECTION 11. Toxicological information .../>>

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

PROPAN-2-OL

LC50 - for Fish EC50 - for Crustacea 4200 mg/l/96h Rasbora heteromorpha 7550 mg/l/48h Daphnia magna

ETHYL ACETATE

LC50 - for Fish Chronic NOEC for Fish Chronic NOEC for Crustacea 2125 mg/l/96h 756 mg/l 24 mg/l

12.2. Persistence and degradability

PROPAN-2-OL Rapidly degradable

ISOBUTYL ACETATE Rapidly degradable

12.3. Bioaccumulative potential

Revision nr.2 Dated 20/09/2023 Printed on 20/09/2023 Page n. 9 / 12

Replaced revision:1 (Dated 18/09/2023)

SECTION 12. Ecological information .../>>

PROPAN-2-OL

Partition coefficient: n-octanol/water 0,05

ETHYL ACETATE

Partition coefficient: n-octanol/water 68 BCF 30

ISOBUTYL ACETATE

Partition coefficient: n-octanol/water 2,3

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: 1993

14.2. UN proper shipping name

ADR / RID: FLAMMABLE LIQUID, N.O.S. IMDG: FLAMMABLE LIQUID, N.O.S. IATA: FLAMMABLE LIQUID, N.O.S.

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3

IMDG: Class: 3 Label: 3

IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA:

Revision nr.2 Dated 20/09/2023 Printed on 20/09/2023 Page n. 10 / 12

Replaced revision:1 (Dated 18/09/2023)

SECTION 14. Transport information .../>>

14.5. Environmental hazards

ADR / RID: NO IMDG: NO IATA: NO

14.6. Special precautions for user

ADR / RID: HIN - Kemler: 33 Limited Quantities: 1 L Tunnel restriction code: (D/E)

Special provision: 274, 601, 640(C-D)

IMDG: EMS: F-E, <u>S-E</u> Limited Quantities: 1 L IATA: Cargo: Maximum quantity: 60 L

IATA: Cargo: Maximum quantity: 60 L Packaging instructions: 364
Passengers: Maximum quantity: 5 L Packaging instructions: 353

Special provision: A3

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

<u>Product</u>

Point 3 - 40
Contained substance
Point 75

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2 Flammable liquid, category 2
Eye Irrit. 2 Eye irritation, category 2
Skin Irrit. 2 Skin irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H315 Causes skin irritation.

PASSIONE BEAUTY S.P.A.

REF 2014 - DL0172 NAIL PREP

Revision nr.2 Dated 20/09/2023 Printed on 20/09/2023 Page n. 11 / 12 Replaced revision:1 (Dated 18/09/2023)

SECTION 16. Other information .../>>

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

ΕN

PASSIONE BEAUTY S.P.A. REF 2014 - DL0172 NAIL PREP Revision nr.2 Dated 20/09/2023 Printed on 20/09/2023 Page n. 12 / 12

Replaced revision:1 (Dated 18/09/2023)

SECTION 16. Other information .../>>

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review: The following sections were modified: 02 / 08 / 11 / 16.